



KF Sandbasic slatted frame with adjustable head and foot sections

- Adjustable head section, shoulder comfort zone and flexible positioning of wooden slats
- Frame height: 40 mm
- Installed height: 50 mm
- With shoulder comfort zone
- With LGA and GS quality certificate
- Especially suitable for latex, foam and pocket sprung mattresses
- Plywood frame and slats, rubber end caps
- With 28 slats, flexible slat positioning end caps, with pressure relieving centre strap, 5 double slats in frame middle, adjustable degree of hardness

Frame size (Width x Length)	890 x 1960 mm
For mattress size (Width x Length)	900 x 2000 mm
Cat. No.	271.75.014

Order qty: 1 pc


Foldaway beds

- A sturdy, torsion-free tubular steel frame, powder coated, in black
- Integrated automatic feet (i.e. automatic extension of feet when opening and automatic retraction of feet when closing)
- Slatted frame support, laminated beech wood frame, light beige lacquered with head and foot adjustment
- 28 resilient wooden slats, light beige, mounted in flexible plastic pockets with cushioning support
- Reinforced foot fitting parts
- Shoulder comfort zone
- Hardness degree regulation, continuously adjustable
- Textile centre strap
- Self lubricating bearings and concealed gas filled struts allow the bed to be raised and lowered with absolute ease
- Premounted bearing plates, gas filled struts and foot linkage enable simple assembly and save time
- LGA quality certificate
- An exact installation drawing is enclosed with every fitting
- **It is essential for foldaway beds to be protected against tipping:** Special purpose securing brackets for this purpose are included in each set; Floors should be checked for suitability
- **Note: Gas filled struts are set for 19 mm front board thickness**



Double foldaway bed

- Recessed front and slatted frame
- Installation height **2100 mm**
- Plinth panel height **75-100 mm**
- 3 Bedding straps included
- 2 Sets of securing brackets included
- Available without mattress only
- Load carrying capacity **60-80 kg**
- Load capacity includes front panel, mattress and bed clothing
- 2 gas pistons included
- The gas filled struts are designed for a certain load capacity; stronger or weaker gas filled struts are available to order for different weights



Lying area	1400 x 2000 mm
Installed height min.	2100 mm
Cat. No.	271.91.135

Order qty: Minimum 5 pcs

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.