



GX53 downlight housings, 240V/7W




For recess mounting



For semi-recess mounting



For surface mounting



Order distributor Cat. No. 826.29.761 and LED lamp separately, shown below

- > For recess or surface mounting - order light to suit required application
- > Recess and semi-recess mounting light:
Screw fixing (fixings not included), for installation in Ø 80 mm hole
- > Surface mounting light:
Screw fixing (fixings included)
- > With 1.5 m lead with connector
- > Thermoplastic, satin chrome finish
- > Extension leads available, shown below
- > Note: LED lamp is not included and must be ordered separately
- > Order qty: 1 pc



Version	Lamp not included
Recessed light	823.63.961
Semi-recessed light	823.63.971
Surface light	823.63.981

GX53 LED lamp, 3W - must be ordered separately, non-dimmable




- > White opaque plastic cover, Ø 74 mm
- > Voltage: 230V. Wattage: 3W
- > Order qty: 1 pc

Distance	120°	3000 K	6500 K
600 mm		108 Lx	145 Lx

Output:	3000 K	6500 K
Light colour:	Warm white	Cool white
Wattage (W):	3	3
Energy efficiency:	A+	A+
Number of diodes:	36	36
Light output (Lm):	130	130
Colour Rendering Index:	88	88

LED colour	3000 K	6500 K
Cat. No.	830.33.738	830.33.737

GX53 distributor



- > 6-way white plastic distributor with 1.5 m lead with 3A mains plug fitted
- > Order qty: 1 pc



Distributor	Cat. No.
6-way	826.29.761

GX53 extension lead



- > With moulded on connectors
- > White plastic
- > Order qty: 1 pc



Length	500 mm	1000 mm	2000 mm
Cat. No.	826.29.751	826.29.752	826.29.753