
Optional accessories for the Loox plug and play system are available to create larger lighting systems where for example more than one switch is required or one switch should control multiple drivers. Please contact our technical support team for advice.

# 24V SYSTEM

## Loox 24V distributor, 3-way, with switching function




- > For adding up to three lights with switching function
- > With 200 mm lead with Loox 24V connector
- > Max. 84W (stand-by power consumption 0.1W)
- > Order qty: 1 pc





Dimensions (L x W x H) 57 x 34 x 18 mm Cat. No. 833.77.723

#### Loox 24V distributor, 6-way, for connecting additional lights to one driver



- > With the 6-way distributor, up to 6 additional lights can be operated from one driver slot
- > With 2.0 m lead with Loox 24V connector
- > Black plastic
- > Order qty: 1 pc





Dimensions (L x W x H) 58.5 x 38 x 18 mm

Cat. No. 833.77.724

#### Loox 24V extension lead



- > Note: Total lead length from driver to light max. 6 m
- > Black plastic
- > Order qty: 1 pc






3.5 A/20 AWG

 Length
 500 mm
 1000 mm
 2000 mm

 Cat. No.
 833.77.712
 833.77.713
 833.77.714

## Loox 24V extension lead, 4-way



- > Convenient extension for additional lights
- > Max. 4 lights per extension lead can be connected, max. 2 extension leads can be coupled
- > Black plastic
- > Order qty: 1 pc





\*\*CH DESIGN 2017, © Häfele U.K. Ltd 2017.

| Length   | 6500 mm    |
|----------|------------|
| Cat. No. | 833.77.813 |


PAGE AMENDED **20.12.17/3** 



Optional accessories for the Loox plug and play system are available to create larger lighting systems where for example more than one switch is required or one switch should control multiple drivers. Please contact our technical support team for advice.

# 24V SYSTEM

## Loox 24V distributor, 3-way, with switching function




- > For adding up to three lights with switching function
- > With 200 mm lead with Loox 24V connector
- > Max. 84W (stand-by power consumption 0.1W)
- > Order qty: 1 pc



Dimensions (L x Cat. No.

x 34 x 18 mm 833.77.723

### Loox 24V distributor, 6-way, for connecting additional lights to o



- to 6 additional lights can be operated -way e driver slo
- lead ith L x 24V connector

nensions (L x W x H) Cat. No.

58.5 x 38 x 18 mm

833.77.724

#### Loox 24V extension lead




- > Note: Total lead length from driver to light max. 6 m
- > Black plastic
- > Order qty: 1 pc



| Length   | 500 mm     | 1000 mm    | 2000 mm    |
|----------|------------|------------|------------|
| Cat. No. | 833.77.712 | 833.77.713 | 833.77.714 |

#### Loox 24V extension lead, 4-way



- > Convenient extension for additional lights
- > Max. 4 lights per extension lead can be connected, max. 2 extension leads can be coupled
- > Black plastic
- > Order qty: 1 pc



| Length   | 6500 mm    |
|----------|------------|
| Cat. No. | 833.77.813 |

Approved by Product Info. Dept.




ICH DESIGN 2017, © Häfele U.K. Ltd 2017.

Optional accessories for the Loox plug and play system are available to create larger lighting systems where for example more than one switch is required or one switch should control multiple drivers. Please contact our technical support team for advice.

# 24V SYSTEM

## Loox 24V distributor, 3-way, with switching function




- > For adding up to three lights with switching function
- > With 200 mm lead with Loox 24V connector
- > Max. 42W (stand-by power consum 0.1W)
- > Order qty: 1 pc



Dimensions (L x 1 x H) 57 x 34 x 18 mm Cat. No. 833.77.723

#### Loox 24V distributor, 6-way, for connecting additional lights to one of ver-



- with the 6-way with a tor p to 6 additional lights can be operated from the cover slow
- > With 2 m les with Loox 24V connector
- Black pla
   ■
   Black pla
   B
  - Jaer ty:

24V

 Dimensions (L x W x H)
 58.5 x 38 x 18 mm

 Cat. No.
 833.77.724

Loox 24V extension lead




- > Note: Total lead length from driver to light max. 6 m
- > Black plastic
- > Order qty: 1 pc



 Length
 500 mm
 1000 mm
 2000 mm

 Cat. No.
 833.77.712
 833.77.713
 833.77.714

#### Loox 24V extension lead, 4-way



- > Convenient extension for additional lights
- > Max. 4 lights per extension lead can be connected, max. 2 extension leads can be coupled
- > Black plastic
- > Order qty: 1 pc



| Length   | 6500 mm    |
|----------|------------|
| Cat. No. | 833.77.813 |


Approved by Product Info. Dept.


97.09.17/1

rch DESIGN 2017, © Häfele U.K. Ltd 2017

Optional accessories for the Loox plug and play system are available to create larger lighting systems where for example more than one switch is required or one switch should control multiple drivers. Please contact our technical support team for advice.

# 24V SYSTEM





- > For adding up to three lights with switching function
- > With 200 mm lead with Loox 24V connector
- > Max. 42W (stand-by power consumption 0.1W)
- > Order qty: 1 pc




Dimensions (L x W x H) 57 x 1 x 18 mm Cat. No. 833.7. 723

### Loox 24V distributor, 6-way, for connecting additional lights to one driver




- > With the 6-way distributor, 10 to 6 addition, light can be operated from one driver slot
- > With 2.0 m lead with 1 V c > to
- > Black plastic
- > Order qt 1 g



Dime...ons (L W x / ) 58.5 x 38 x 18 mm 833.77.724

#### Loox 24V extension lea 1, 4-way



- > Convenient extension for additional lights
- > Max. 4 lights per extension lead can be connected, max. 2 extension leads can be coupled
- > Black plastic
- > Order qty: 1 pc



 Length
 6500 mm

 Cat. No.
 833.77.813

PAGE CREATED 07.09.17 ICH DESIGN 2017, © Häfele U.K. Ltd 2017.