

IXCONNECT RED JIG SUPPLEMENTARY PARTS

Supplementary parts for red jig basic jig and supplementary jigs shown on pages 42-43B.

Red jig supplementary parts



- A Red jig drill guides for connectors and series drilled holes
 - B Depth gauges, supplied with 1x depth gauge, stop ring, spiral spring
 - C Marking pin Ø 3/5 mm
 - D Stop rings for HS twist drill bit Ø 8 mm or Ø 10 mm
 - E Inserts for 5, 8, 10 or 11 mm
 - F Marking gauge
 - G Stop plate with 2 special screws
 - H Twist drill bit for wood, HM, total length 130 mm, shank Ø 8 mm (depth gauge 15)
 - I Multi-spur drill bits, HM, total length 130 mm, shank Ø 10 mm (depth gauge 32 and 48)
 - J Multi-spur drill bits, HM/HW, 3-spur, total length 130 mm, shank Ø 10 mm (depth gauge 32 and 48) Ø 20 mm version with countersinker for wood thickness 19 mm
 - K Twist drill bits for wood, HS, total length 110 mm
 - L Universal bit holder with quick release chuck, length 60 mm, 1/4" chuck, 1/4" drive, with permanent magnet
- > Order qty: 1 pc



Item	Cat. No.
A Guide for Minifix 12/15	001.25.660
Guide for Maxifix, tightening distances 55/35 mm	001.25.643
Guide for Rafix 20, Tab 18, OneFix	001.25.625
Guide for hole systems at 37/69 mm intervals	001.25.620
Guide for Ø 35 concealed hinges, 48/6 pattern	001.25.731
Guide for Ø 35 concealed hinges, 45/9.5 pattern	001.25.732
B Depth gauge 15 mm, up to drill bit Ø 3-10 mm	001.25.770
Depth gauge 132 mm, up to drill bit Ø 12-25 mm	001.25.771
Depth gauge 148 mm, up to drill bit Ø 26-40 mm	001.25.772
C Marking pin Ø 3/5 mm	001.25.766
D Stop ring for HS twist drill bit Ø 8 mm	001.42.683
Stop ring for HS twist drill bit Ø 10 mm	001.42.693
E Insert 5 mm	001.25.763
Insert 8 mm	001.25.760
Insert 10 mm	001.25.761
Insert 11 mm	001.25.762
F Marking gauge	001.27.060
G Stop plate with 2 special screws	001.25.063
H Twist drill bit Ø 3 mm	001.06.682
Twist drill bit Ø 5 mm	001.06.683
Twist drill bit Ø 8 mm	001.06.686
Twist drill bit Ø 10 mm	001.06.687
I Multi-spur drill bit, HM, Ø 12 mm	001.06.661
Multi-spur drill bit, HM, Ø 15 mm	001.06.662
Multi-spur drill bit, HM, Ø 35 mm	001.06.669
J Multi-spur drill bit, HM/HW, Ø 18 mm	001.24.454
Multi-spur drill bit, HM/HW, Ø 20 mm	001.24.417
K Twist drill bit, Ø 8 mm	001.20.508
Twist drill bit, Ø 10 mm	001.20.510
L Bit holder	006.37.250



Red jig basic jig and supplementary jigs are shown on pages 42-43B

Approved by Product Info. Dept.

PAGE AMENDED
15.11.18/1

FOR OUR FULL PRODUCT RANGE VISIT HAFELE.CO.UK

IXCONNECT RED JIG SUPPLEMENTARY PARTS

Red jig supplementary parts



> Supplementary parts for red jig basic jig and supplementary jigs shown on pages 42-43

- A Minifix 12/15 drill guide
 - B Depth gauge 15 mm
 - C Drill bit, Ø 5 mm
 - D Drill guide for group of holes
 - E Depth gauge 32 mm
 - F HM multi-spur drill bit, Ø 15 mm
 - G Marking pin 3/5 mm
 - H Marking gauge
 - I Twist drill bit, Ø 8 mm
 - J Stop ring, 8 mm
 - K Bit holder
 - L HM multi-spur drill bit, Ø 20 mm
 - M HM multi-spur drill bit, Ø 18 mm
- > Order qty: 1 pc

SUPERSEDED



Item	Cat. No.
A Minifix 12/15 drill guide	001.25.660
B Depth gauge 15 mm	001.25.770
C Drill bit, Ø 5 mm	001.06.683
D Drill guide for group of holes	001.25.620
E Depth gauge 32 mm	001.25.771
F HM multi-spur drill bit, Ø 15 mm	001.06.662
G Marking pin 3/5 mm	001.25.766
H Marking gauge	001.27.060
I Twist drill bit, Ø 8 mm	001.20.508
J Stop ring, 8 mm	001.42.683
K Bit holder	006.37.250
L HM multi-spur drill bit, Ø 20 mm	001.24.417
M HM multi-spur drill bit, Ø 18 mm	001.24.454



Red jig basic jig and supplementary jigs are shown on pages 42-43