HAWA-JUNIOR 40/Z AND 40/B SLIDING DOOR SYSTEM


Junior 40/Z is a vertically adjustable sliding door fitting for light to medium weight interior doors, for top quality joinery and partitioning. HAWA-Junior 40/B is suitable for low and restricted headroom applications.


- > HAWA-Junior 40/Z
- > Range:


Max. door weight 40 kg Min. door thickness 22 mm


- > Height adjustment ±3 mm
- > Installation drawing reference 17689












Easy to install

The two-way mounting plate allows the sliding door to be taken off or suspended in two different ways:

Fig. 2 - Front mounting





- > HAWA-Junior 40/B
- > For low and restricted headroom applications
- > Range:


Max. door weight 40 kg


Min. door thickness 30 mm

Max. door height normally 2.1 m

- > Height adjustment ±3 mm
- > Installation drawing reference 17689











Complete sets for 1 door shown below or tracks and fitting sets available to order separately, shown on page 43

Hawa-Junior 40/Z and 40/B complete sets



Hawa-Junior 40/B sets include a side fixing profile, track fixing set and profile trim caps for side fixing, refer to page 51 for details

- > Hawa Junior 40/Z and 40/B sets include 1x 2.0 m length track and all fittings required for 1 door, including 1 additional track stopper
- > Order qty: 1 set

Complete fitting se	et for 1 doorJunior 40/Z	Junior 40/B	
Cat. No.	940.40.010	940.40.011	

We reserve the right to alter specifications without TCH AH 2019, @ Häfele U.K. Ltd 2019. Dimensional data not binding.

HXFEL

HAWA-Junior 40 tracks






Top track side fixing profile is available, shown on page 43

- > With screw holes for soffit fixing
- > Two top tracks are mounted side by side for double or multiple doors
- > Silver anodised aluminium
- > Order qty: 1 pc




Length	2.0 m	3.0 m	
Cat. No.	940.40.200	940.40.300	

HAWA-Junior 40/Z and 40/B fitting sets









The retaining force can be adjusted with an allen key

- > Fitting sets, for one door
- B Track stopper, 18 x 59 x 21 mm, for adjustable mounting in top track, zinc alloy housing, adjustable retaining force
- C HAWA-Junior 40/Z trolley hanger, sleeve bearing mounted Ø 25 mm high-grade polyamide tandem rollers, aluminium carriage with zinc-alloy mounting plate, fixings included
- D HAWA-Junior 40/B trolley hanger, sleeve bearing mounted Ø 25 mm high-grade polyamide tandem rollers, with 25 x 185 x 20 mm retainer profile and suspension plate, M8 hanger pendant and tension bolt, fixings included
- E Locking wrench, for suspension profile
- F Profile plugs, grey plastic
- G Guide, rattle proof, for screw mounting to floor, black plastic, 24 x 60 x 34 mm
- > Order qty: 1 set





Fitting set for 1 door	Junior 40/Z	Junior 40/B
B Track stopper	2 pcs	2 pcs
C Junior 40 trolley hanger	2 pcs	-
D Junior 40/B trolley hanger	-	2 pcs
E Locking wrench	-	1 pc
F Profile plugs	-	2 pcs
G Guide	1 pc	1 pc
Cat. No.	940.41.016	940.41.017
Additional items		
Item B		940.40.041
Item G		940.40.031

HAWA-Junior alternative light duty guiding with continuous aluminium channel



TCH AH 2019, @ Häfele U.K. Ltd 2019. Dimensional data not binding. We reserve the right to alter specifications without notice.

- > For HAWA-Junior 40/80
- > Recommended for doors over 1000 mm wide
- I Guide, steel plate with nylon blade, 25 x 60 x 23.5 mm, 2 pcs required per door
- J Channel, pre-drilled for counter sunk screws, bright aluminium
- > Order qty: 1 pc

±30	0
15 15	15

Guide			
Item I		409.12.990	
Channel	2.1 m	3.0 m	
Item J	409.14.010	409.14.029	